

# ECAD / MCAD Collaboration Implementation Guidelines

Version 3.5, 01.07.2018

Status: released



## **Abstract**

This Implementation Guideline accompanies the prostep ivip PSI5 Recommendation for ECAD/MCAD-Collaboration.

## Disclaimer

prostep ivip Certification Guidelines (PSI Certification Guidelines) are available for general use. Anyone using these recommendations is responsible for ensuring that they are used correctly.

This PSI Certification Guidelines gives due consideration to the prevailing state-of-the-art at the time of publication. Anyone using PSI Certification Guidelines must assume responsibility for his or her actions and acts at their own risk. The prostep ivip Association and the parties involved in drawing up the PSI Certification Guidelines assume no liability whatsoever.

We request that anyone encountering an error or the possibility of an incorrect interpretation when using the PSI Recommendation should contact the prostep ivip Association ([psi-issues@prostep.com](mailto:psi-issues@prostep.com)) immediately so that any errors can be rectified.

## Copyright

- I. All rights on this PSI Documentation, in particular the copyright rights of use and sale such as the right to duplicate, distribute or publish the Documentation remain exclusively with the prostep ivip Association and its members.
- II. The PSI Documentation may be duplicated and distributed unchanged, for instance for use in the context of creating software or services.
- III. It is not permitted to change or edit this PSI Documentation.
- IV. A suitable notice indicating the copyright owner and the restrictions on use must always appear.

# Contents

## Table of Contents

1 General .....	9
1.1 Objectives of the Implementation Guidelines .....	9
1.2 Document structure.....	9
2 Requirements for ECAD/MCAD .....	9
3 Overview of use cases discussed in Implementation guidelines .....	10
3.1 Use cases covered within implementer guidelines .....	10
3.2 Test cases.....	12
4 Introduction to EDMD protocol .....	13
5 Guideline for instantiation ECAD/MCAD collaboration in XML .....	14
5.1 Representation of “item descriptions” (EDMDataSet) in XML.....	15
5.1.1 Representation of an item .....	16
5.1.2 Use “correct” classification for an item .....	20
5.1.3 Representation of the shape of an item in “2.5 D” .....	24
5.1.4 XML representation of an EDMArc.....	28
5.1.5 XML representation of an EDMBSplineCurve .....	29
5.1.6 Instantiation of an EDMCircle3Point.....	30
5.1.7 XML representation of an EDMCircleCenter .....	31
5.1.8 XML representation of an EDMEllipse .....	32
5.1.9 XML representation of an EDMParabola.....	33
5.1.10 XML representation of an EDMPolyLine .....	34
5.1.11 XML representation of an EDMCompositeCurve .....	35
5.1.12 Representation of the shape of an item as external file.....	36
5.1.13 XML representation of items of a PCB board (exemplary) .....	37
5.1.14 Exemplary XML representation of an item .....	38
5.1.15 XML representation of PCB board with components (assembly) .....	39
5.2 Representation of “SendInformation” message in XML.....	40
5.3 Representation of “SendChanges” message in XML .....	40
5.4 Enhanced item specification: “How to” for special ECAD features.....	45
5.4.1 How to represent traces and copper areas .....	45
5.4.2 How to represent flexible areas of PCB board .....	49
5.4.3 Board layer modelling / inner stratum feature .....	54
5.4.4 Board layer modelling with dielectric layers .....	55
5.4.5 Inner stratum feature .....	59
5.4.6 Transaction-History .....	61
5.4.7 How to model “placement keepouts”.....	63
5.4.8 How to model “Route Keepouts of type Trace/Via”.....	64
5.4.9 How to model “Plane Keepouts” .....	65

5.4.10 How to model “Mounting Hole (Plated and non-plated)” .....	65
5.4.11 How to model a “milled cutout” (created by a drill).....	66
5.4.12 How to model “Partially Plated Cutouts” .....	68
5.4.13 How to represent stiffener .....	69
5.4.14 How to represent placement group area.....	70
5.4.15 How to define Comp_Pins.....	70
5.4.16 How to represent other outline / user area layer.....	73
5.4.17 Use message file compression (*.idz).....	74
5.4.18 z-Offset for Item instance .....	74
6 Instantiation of test cases .....	75
6.1 Test Case 1-1: “Support of shape representations” .....	75
6.2 Test Case 1-2: “Definition of board baseline B” .....	77
6.3 Test Case 2-1: Addition of new items (Change 1) .....	77
6.3.1 How to represent addition of item instances? .....	78
6.4 Test case 2-2: Removal of items (Change 2) .....	78
6.4.1 How to represent removal of item instances? .....	79
6.5 Test case 2-3: Movement of items (Change 3) .....	79
6.5.1 How to represent movement of item instances? .....	80
6.6 Test case 2-4: Modification of items (Change 4) .....	80
6.6.1 How to represent modification of item shape? .....	81
6.7 Test case 2-5: Replacement of items (Change 5) .....	81
6.7.1 How to represent replacement of items? .....	82
7 Terms for EDMD property .....	82

## Figures

Figure 1: Structure of implementer guidelines.....	9
Figure 2: Use Cases covered within implementer guidelines .....	11
Figure 3: Types of communication .....	13
Figure 4: Instantiation of Use Cases .....	14
Figure 5: Structure of EDMD messages.....	15
Figure 6: Structure of DataSet section .....	15
Figure 7: Overview on section giving advice on how items should be instantiated in EDMD schema .....	16
Figure 8: Representation of two instances of a PCB package in EDMD .....	17
Figure 9: Representation of instances of board components.....	18
Figure 10: XSD schema for an item .....	18
Figure 11: Description of an item instance .....	19
Figure 12: Exemplary PCB board with components and design features.....	19
Figure 13: Possible instantiation of a PCB board.....	20
Figure 14: Three “parameter” for classifying an item .....	21
Figure 15: Representation of a shape of an item by combine several “translation bodies” (“OR” operator). .	24
Figure 16: Usage of upper/lower bound and thickness.....	24
Figure 17: Instantiation of combination of „translation bodies“ (example) .....	25
Figure 18: Representation of a shape of an item by “cut-out” another body (“NAND” operator).....	25
Figure 19: Describe a closed curve of by combination of several other curves .....	26
Figure 20: Body with a composite curve as footprint .....	26
Figure 21: XML representation of an arc.....	28
Figure 22: XML representation of a B-Spline .....	29
Figure 23: XML representation of a circle described by three points.....	30
Figure 24: XML representation of a circle described by center point and diameter.....	31
Figure 25: XML representation of an Ellipse .....	32
Figure 26: XML representation of a parabola.....	33
Figure 27: XML representation of a poly line.....	34
Figure 28: XML representation of a composite curve .....	35
Figure 29: XSD schema for representing the shape of an item as external file.....	36
Figure 30: Instantiation for implicit representation of an item’s shape .....	36
Figure 31: Overview: Instantiation of the board.....	37
Figure 32: XML representation of a mounting hole .....	38
Figure 33: Representation of a board with components .....	39
Figure 34: XML representation of SendInformation message (root).....	40
Figure 35: Representation of a change (here: movement of a component) .....	41
Figure 36: XML representation of SendChange message (root) .....	41
Figure 37: Definition of a single change .....	42
Figure 38: Head section of SendChanges message in XML .....	42

Figure 39: Example for instantiation of the "Changes" section ..... 43

Figure 40: Description of items in "change" section is done in "Dataset" section ..... 44

Figure 41: Interpretation of unbound lower/upper bound of keep-out ..... 63

Figure 42: Representation of a "milled cutout" ..... 67

Figure 43: Representation of a "PartiallyPlatedCutout" ..... 69

Figure 44: Verify support of different kinds of "explicit" shape representation ..... 76

Figure 45: Verify definition of initial base line which contains main item types for collaboration ..... 77

Figure 46: Verify addition of new items ..... 78

Figure 47: Verify removal of items from board ..... 79

Figure 48: Verify movements of items ..... 80

Figure 49: Verify modification of items ..... 81

Figure 50: Verify replacement of items ..... 82

## Tables

Table 1: Test cases for certification process ..... 12

Table 2: EDMD ItemShape classes and their detailed types ..... 22

Table 3: Values for “classification parameters” of an item ..... 23

Table 4: Overview on available curve types ..... 27

Table 5 Property name and unit to be used based on IDF 3.5 ..... 83