



Automated Functional Data Exchange in the Automobile Industry

prostep ivip PSI 20/VDA 5550 Part 3.3

Automated Functional Data Exchange
in the Automobile Industry (FDX)

Part 3.3: Wheel Brake

Abstract Part 3.3: Wheel Brake

This prostep ivip (PSI) / VDA recommendation was drawn up by the Functional Data Exchange (FDX) working group and defines a standard format and a machine-readable specification of a data model/data format for the transfer of functional data (e.g., characteristic diagrams, characteristic curves, characteristic values) between customers and their suppliers.

It enables the exchange of highly structured data. This recommendation aims at facilitating consistent and efficient implementation of these processes in the automotive industry.

Objectives:

- Harmonization of the exchange of functional data between OEMs and suppliers
- Improved quality and availability of functional data for CAE/simulation purposes
- Elimination of discrepancies in functional data between ordered and delivered data
- Higher level of automation for data generation, data exchange and data use

Disclaimer

prostep ivip documents (PSI documents) are available for anyone to use. Anyone using these documents is responsible for ensuring that they are used correctly.

This PSI documentation gives due consideration to the prevailing state-of-the-art at the time of publication. Anyone using PSI documentations must assume responsibility for his or her actions and acts at their own risk. The prostep ivip Association and the parties involved in drawing up the PSI documentation assume no liability whatsoever.

We request that anyone encountering an error or the possibility of an incorrect interpretation when using the PSI documentations contact the prostep ivip Association (psi-issues@prostep.org) so that any errors can be rectified.

Copyright

- I. All rights to this PSI documentation, in particular the right to reproduction, distribution and translation remain exclusively with the prostep ivip Association and its members.
- II. The PSI documentation may be duplicated and distributed unchanged in case it is used for creating software or services.
- III. It is not permitted to change or edit this PSI documentation.
- IV. A notice of copyright and other restrictions of use must appear in all copies made by the user.

Table of Contents

| | |
|--|-----------|
| 1 Introduction | 5 |
| 1.1 Background and objectives | 5 |
| 1.2 Structure of the VDA recommendation | 5 |
| 1.3 Formatting conventions | 5 |
| 2 Definitions | 6 |
| 2.1 Coordinate systems | 6 |
| 2.2 Conventions for operational signs | 6 |
| 3 Part Specific Information {AddInfoPartSpec} | 6 |
| 4 Test Equipment Setup {Test Equipment} | 8 |
| 5 Test Equipment Parameters (part-specific) {Test Sequence} | 9 |
| 5.1 General | 9 |
| 5.1.1 Classification | 9 |
| 5.1.2 Specifying data points | 9 |
| 5.2 Preconditioning – Dynamometer {TPmDynoPC} | 9 |
| 5.2.1 Bedding-in or burnishing procedure of wheel brakes {TPmDynoPC} | 9 |
| 5.3 Test programs | 9 |
| 5.3.1 Measurement – Dynamometer {TpmDynoMS} | 9 |
| 5.3.2 Wear Test Procedure SAE-J2707 {TPmBrkWearMS} | 12 |
| 5.3.3 Volume Consumption {TPmVolConsumption} | 12 |
| 5.4 Environmental Parameters {EnvironmentPara} | 13 |
| 5.4.1 Environmental Temperature {EnvironTempPara} | 13 |
| 5.4.2 Air Flow {EnvironAirFlowPara} | 13 |
| 6 Instance Data | 14 |
| 6.1 Functional Data (part-specific) {FunctionalData} | 14 |
| 6.1.1 Friction value characteristic | 14 |
| 6.1.2 Brake lining wear characteristic | 16 |
| 6.1.3 Low velocity friction curves | 17 |
| 6.1.4 Volume Consumption of Brake Caliper | 18 |
| 6.2 Derived Characteristics (part-specific) | 19 |
| 7 Closing Remarks | 20 |
| 8 Table of Attributes | 20 |

Figures

| | |
|--|----|
| Figure 6.1: Geometrical terms of a disc brake | 14 |
| Figure 6.2: Friction coefficient at pressure applies | 14 |
| Figure 6.3: Friction coefficient over temperature | 15 |
| Figure 6.4: Field of friction coefficient over pressure and temperature | 16 |
| Figure 6.5: Velocity dependent characteristics of the friction coefficient | 18 |

Tables

| | |
|---|----|
| Table 6.1: Example of MapBrkFricVal | 16 |
| Table 6.2: Example of brake lining wear characteristic | 16 |
| Table 6.3: Example of a velocity dependent friction coefficient measurement | 17 |
| Table 6.4: Example of volume consumption (CurveVolConsCaliper) | 18 |
| Table 6.5 Characteristic values from AK Master | 19 |